


Fashion-REFLECT™



REMOVE liner from adhesive side of material before cutting. feed material into cutter so that the carrier is on the bottom



PREHEAT AND POSITION— Preheat garment for 10 seconds. Position weeded design on garment with the carrier side up (*reads left to right*). Place a Kraft Paper cover sheet over carrier before pressing.




CUT LOGO, words or numbers in reverse (*mirror image*).



HEAT APPLY— Temperature: 305°F; 150°C
 Time: 5 seconds
 Pressure: medium
 #4 on Hotronix®

PEEL WARM — Garment must still be warm to remove carrier successfully.



WEED away excess material leaving only the desired graphic on the carrier.



FINAL APPLICATION— Cover with Kraft Paper and reseal for 5 seconds.

Extremely thin and stretchable, CAD-CUT® Fashion-REFLECT™ has a very soft hand and is perfect for creating fine details and modern effects on garments. This material is suited for heat application onto all textiles except coated nylon.

Recommended Fabrics

100% cotton
 100% polyester
 Poly/cotton blends
 Lycra®/ Spandex blends
 Woven nylon
 Nylon knits
 Nylon meshes - micro, tricot, mini, reversible
 Polyester knits
 Polyester mesh
 Poly/foam & cotton caps
 Satin
 Cordura®

Accessories Required

Kraft Paper or Teflon® Sheet EZ
 Weeder® or Tweezers

Cutting Notes

You should always test cut prior to any production run. For optimal cutting and weeding, maintain a line thickness of at least 1/8" for lettering & logos.

Care Instructions

Machine wash using mild detergent. Do not use bleach. Dry at a normal dryer setting on household machines. Do not iron directly onto Fashion-REFLECT. Do not dry clean

Multi-Color Designs

Before the final application, align second color, heat apply, & peel carrier. Repeat for additional colors. Finish with final application step.

CAD-CUT® Fashion-REFLECT™ materials offer improved visibility under certain lighting conditions. The silver Fashion-REFLECT™ is the only color in this line which meets the reflectivity requirements of the ANSI/ISEA or that of any other national/international safety regulations.

CUTTER GUIDELINES

CUTTER	BLADE	FORCE	OFFSET	SPEED
Roland GX-24	60° / 45°	80g / 90g	.60 / .25	50cm/s
Ioline 100	45°	140g	.15	75%
Ioline 300	30°	120g	.15	25%

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

CAD-CUT, Fashion-REFLECT, & Hotronix are trademarks & ® trademarks of Stahls' ID Direct™ with one or more patents or patents pending.
 © Stahls' ID Direct™ 2010 - All International Rights Reserved